CLAIMS:

5

15

- 1. Metal halide lamp suitable as projection lamp, for instance as a vehicle headlamp comprising a discharge vessel surrounded by an outer envelope with clearance and having a ceramic wall which encloses a discharge space filled with a filling comprising an inert gas, such as xenon (Xe), and an ionizable salt, wherein in said discharge space two electrodes are arranged whose tips have a mutual interspacing so as to define a discharge path between them, characterized in that said ionizable salt comprises NaI, TII, CaI₂ and XI₃, wherein X is selected from the group comprising rare earth metals.
- 2. Metal halide lamp according to claim 1, wherein X is selected from the group comprising Ce, Pr, Lu, Nd.
 - 3. Metal halidelamp according to claim 1 or 2, wherein X is Ce and wherein the molar percentage ratio $CeI_3/(NaI + TII + CaI_2 + CeI_3)$ lies between 0 and 10%, in particular between 0,5 and 7%, more in particular between 1 and 6.
 - 4. Metal halidelamp according to claim 1, 2 or 3, wherein X is Ce and wherein the molar percentage ratio $CaI_2/(NaI + TII + CaI_2 + CeI_3)$ lies between 20 and 90%, in particular between 35 and 85%, more in particular between 45 and 80%.
- 5. Metal halidelamp according to any of the preceding claims 1 through 4, wherein the amount of NaI, TII, CaI₂ and XI_n lies between 0,005 and 0,5 g/cm³, in particular between 0,025 and 0,3 g/cm³.
- 6. Metal halidelamp according to any of the preceding claims 1 through 5, wherein the filling comprises Hg.
 - 7. Metal halide lamp according to any of the preceding claims 1 through 6 to be used as projection lamp, in particular in a vehicle headlamp.